

VIIRS 375m Active Fire Science Processing Algorithm (VFIRE375_SPA) User's Guide

Version 2.2.0

March 2016



**GODDARD SPACE FLIGHT CENTER
GREENBELT, MARYLAND**

VIIRS 375m Active Fire Science Processing Algorithm

VFIRE375_SPA

General

The NASA Goddard Space Flight Center's (GSFC) Direct Readout Laboratory (DRL), Code 606.3 developed this software for the International Polar Orbiter Processing Package (IPOPP). IPOPP maximizes the utility of Earth science data for making real-time decisions by giving fast access to instrument data and derivative products from the Suomi National Polar-orbiting Partnership (SNPP), Aqua, and Terra missions and, in the future, the Joint Polar Satellite System (JPSS) mission.

Users must agree to all terms and conditions in the Software Usage Agreement on the DRL Web Portal before downloading this software.

Software and documentation published on the DRL Web Portal may occasionally be updated or modified. The most current versions of DRL software are available at the DRL Web Portal:

<http://directreadout.sci.gsfc.nasa.gov/?id=software>

Questions relating to the contents or status of this software and its documentation should be addressed to the DRL via the Contact DRL mechanism at the DRL Web Portal:

<http://directreadout.sci.gsfc.nasa.gov/?id=dspContent&cid=66>

Algorithm Wrapper Concept

The DRL has developed an algorithm wrapper to provide a common command and execution interface to encapsulate multi-discipline, multi-mission science processing algorithms. The wrapper also provides a structured, standardized technique for packaging new or updated algorithms with minimal effort.

A Science Processing Algorithm (SPA) is defined as a wrapper and its contained algorithm. SPAs will function in a standalone, cross-platform environment to serve the needs of the broad Direct Readout community. Detailed information about SPAs and other DRL technologies is available at the DRL Web Portal.

Software Description

This software package contains the Visible Infrared Imaging Radiometer Suite (VIIRS) 375m Active Fire Science Processing Algorithm (VFIRE375_SPA). This algorithm primarily uses brightness temperatures derived from bands I04 and I05 to detect fires. The algorithm takes as input VIIRS 375m Science Data Record (SDR) files, along with the associated terrain-corrected geolocation file, and identifies active fires. Additionally, the algorithm may also optionally take as input VIIRS M13 and IVCDB SDR files in order to process nighttime data located over the South Atlantic Anomaly. The outputs are a two-dimensional fire mask in Hierarchical Data Format (HDF) and a fire location text file. The SPA functions in two modes: standalone, or as an IPOPP plug-in.

Software Version

Version 1.5 of the DRL algorithm wrapper was used to package the SPA described in this document. The SPA uses version 2.2.0 of the VFIRE375 algorithm.

This software will execute on a 64-bit computer and has been tested on computers with 32GB of RAM, with the following operating systems:

- a) Fedora 20 X86_64;
- b) CentOS Linux 7 X86_64;
- c) OpenSUSE Linux 13.2 X86_64;
- d) Kubuntu 14.04 X86_64.

Copyright 1999-2007, United States Government as represented by the Administrator for the National Aeronautics and Space Administration. All Rights Reserved.

Credits

The VFIRE375 SPA was developed by the NASA Land Science Team in collaboration with the DRL at NASA/GSFC. The software conforms with the International Land Direct Readout Coordinating Committee (ILDRCC) data requirements.

Prerequisites

To run this package, you must have the Java Development Kit (JDK) or Java Runtime Engine (JRE) (Java 1.6.0_25 or higher) installed on your computer, and have the Java installation bin/ subdirectory in your PATH environment variable. This package contains 64-bit binaries statically pre-compiled on an x86-compatible 64-bit computer running under CentOS 7, using gcc 4.5.1.

Program Inputs and Outputs

The VFIRE375 algorithm takes as input VIIRS I01, I02, I03, I04, and I05 SDRs, and I-band terrain-corrected geolocation HDF files. Additionally, VIIRS M13 SDR and IVCDB HDF files may be optionally provided in order to enable processing of nighttime data located over the South Atlantic Anomaly (these additional inputs are not required for nighttime data located anywhere else). The algorithm outputs the VIIRS 375m Active Fires HDF file and the Fire Location text file.

Installation and Configuration

Installing as a Standalone Application:

Download the VFIRE375_2.2.0_SPA_1.5.tar.gz and VFIRE375_2.2.0_SPA_1.5_testdata.tar.gz (optional) files into the same directory.

Decompress and un-archive the VFIRE375_2.2.0_SPA_1.5.tar.gz and VFIRE375_2.2.0_SPA_1.5_testdata.tar.gz (optional) files:

```
$ tar -xzf VFIRE375_2.2.0_SPA_1.5.tar.gz
$ tar -xzf VFIRE375_2.2.0_SPA_1.5_testdata.tar.gz
```

This will create the following subdirectories:

```
SPA
  VFIRE375
    algorithm
    ancillary
    station
    testdata
    testscripts
    wrapper
```

Installing into an IPOPP Framework: This SPA can also be installed dynamically into an IPOPP framework to automate production of VIIRS 375m Active Fires and Fire Location text file data products. The SPA installation process will install its SPA service(s) into IPOPP. An SPA service is an IPOPP agent that provides the mechanism necessary for running an SPA automatically within the IPOPP framework. Once this SPA is installed, users must enable the SPA service(s) corresponding to this SPA along with any other prerequisite SPA service(s). Instructions for installing an SPA and enabling its services are contained in the IPOPP User's Guide (available on the DRL Web Portal). The SPA services associated with this SPA are listed in Appendix A.

Software Package Testing and Validation

The testscripts subdirectory contains test scripts that can be used to verify that your current installation of the SPA is working properly, as described below. Note that the optional VFIRE375_2.2.0_SPA_1.5_testdata.tar.gz file is required to execute these testing procedures.

Step 1: cd into the testscripts directory.

Step 2: There is a script named run-VFIRE375.sh inside the testscripts directory.

To run the VFIRE375 algorithm, use

```
$ ./run-VFIRE375.sh
```

A successful execution usually requires 1 minute or more, depending on the speed of your computer and the size of the input. If everything is working properly, the scripts will terminate with a message such as:

```
Output viirs.activefires375 is /home/ipopp/drl/SPA/VFIRE375/testdata/output/VF375.hdf
Output viirs.fireloc375 is /home/ipopp/drl/SPA/VFIRE375/testdata/output/FireLoc375.txt
```

You can `cd` to the output directory to verify that the science products exist. Test output product(s) are available for comparison in the `testdata/output` directory. These test output product(s) were generated on a 64-bit PC architecture computer running CentOS 7. The output products serve as an indicator of expected program output. Use a comparison utility (such as `diff`, `hdiff`, etc.) to compare your output product(s) to those provided in the `testdata/output` directory. Locally generated files may differ slightly from the provided output files because of differences in machine architecture or operating systems.

If there is a problem and the code terminates abnormally, the problem can be identified using the log files. Log files are automatically generated within the directory used for execution. They start with `stdfile*` and `errfile*`. Other log and intermediate files may be generated automatically within the directory used for execution. They are useful for traceability and debugging purposes. However it is strongly recommended that users clean up log files and intermediate files left behind in the run directory before initiating a fresh execution of the SPA. Intermediate files from a previous run may affect a successive run and produce ambiguous results. Please report any errors that cannot be fixed to the DRL.

Program Operation

In order to run the package using your own input data, you can either use the run scripts within the wrapper subdirectories, or modify the test scripts within the `testscripts` subdirectory.

To Use the Run Script

Identify the 'run' script: The wrapper directory within this package contains one subdirectory named `VFIRE375`. The subdirectory contains an executable called `'run'`. Execute `'run'` within the correct wrapper subdirectory to generate the corresponding product. For instance, the `'run'` within `wrapper/VFIRE375` is used for creating `VFIRE375` outputs. Note that to execute `'run'`, you need to have `java` on your path.

Specify input parameters using <label value> pairs: To execute the `'run'` scripts, you must supply the required input and output parameters. Input and output parameters are usually file paths or other values (e.g., an automatic search flag). Each parameter is specified on the command line by a `<label value>` pair. Labels are simply predefined names for parameters. Each label must be followed by its actual value. Each process has its own set of `<label value>` pairs that must be specified in order for it to execute. Some of these pairs are optional, meaning the process would still be able to execute even if that parameter is not supplied. The two types of `<label value>` pairs that the `VFIRE375_SPA` uses are:

- a) Input file label/values. These are input file paths. Values are absolute or relative paths to the corresponding input file.
- b) Output file label/values. These are output files that are produced by the SPA. Values are absolute or relative paths of the files you want to generate.

The following tables contain labels, and their descriptions, required by the VFIRE375_SPA.

Input File Labels	Description	Source
viirs.gitco	VIIRS I-Band Terrain-Corrected Geolocation input HDF file path	<ol style="list-style-type: none"> 1. The C-SDR_SPA may be used to create these products. 2. Real time products over the eastern US region are available from the DRL ftp site at: <a href="ftp://is.sci.gsfc.nasa.gov/gsfcddata/npp/viirs/level1/<GITCO SV xx SVM13 IVCDB>_npp_dyymmdd_thhmmssS_ehhmmssS*.h5">ftp://is.sci.gsfc.nasa.gov/gsfcddata/npp/viirs/level1/<GITCO SV xx SVM13 IVCDB>_npp_dyymmdd_thhmmssS_ehhmmssS*.h5 Where yyyy, mm, dd represents the year, month, and day of month for the start of the swath; the first hh, mm, ss, S represents the hour, minutes, seconds, and 10th of a second for the start of the swath and the second hh, mm, ss, S represents the end time of the swath. (xx = 01 to 05) 3. VIIRS I-Band SDR, I-Band Terrain-Corrected Geolocation, and M-Band SDR products for other locations and times are available for download at www.class.noaa.gov
viirs.svi01	VIIRS 375m I01 band SDR input HDF file path	
viirs.svi02	VIIRS 375m I02 band SDR input HDF file path	
viirs.svi03	VIIRS 375m I03 band SDR input HDF file path	
viirs.svi04	VIIRS 375m I04 band SDR input HDF file path	
viirs.svi05	VIIRS 375m I05 band SDR input HDF file path	
viirs.svm13 (Optional)	VIIRS 750m M13 band SDR input HDF file path	
viirs.ivcdb (Optional)	VIIRS Calibrator Dual-Gain IP input HDF file path	

Output File Labels	Description	Output Format Description
viirs.activefires375	VIIRS 375m Active Fires output HDF file path	Please refer to the "vfire375_users_guide.pdf" document in the algorithm/docs/ directory within the VFIRE375_SPA package
viirs.fireloc375	VIIRS 375m Fire Location output text file path	

Execute the 'run': The following script shows an example of a command line to run the VFIRE375 algorithm from the testscripts directory:

```
$ ../wrapper/VFIRE375/run \
viirs.gitco ../testdata/input/GITCO_npp_d20140901_t1738560_e1740201_b14746_c20140908200715043541_noaa_ops.h5 \
```

```
viirs.svi01 ../testdata/input/SVI01_npp_d20140901_t1738560_e1740201_b14746_c20140908200814185302_noaa_ops.h5 \  
viirs.svi02 ../testdata/input/SVI02_npp_d20140901_t1738560_e1740201_b14746_c20140908200817203819_noaa_ops.h5 \  
viirs.svi03 ../testdata/input/SVI03_npp_d20140901_t1738560_e1740201_b14746_c20140908200743066611_noaa_ops.h5 \  
viirs.svi04 ../testdata/input/SVI04_npp_d20140901_t1738560_e1740201_b14746_c20140908200756074531_noaa_ops.h5 \  
viirs.svi05 ../testdata/input/SVI05_npp_d20140901_t1738560_e1740201_b14746_c20140908200946032012_noaa_ops.h5 \  
viirs.activefires375 ../testdata/output/VF375.hdf \  
viirs.fireloc375 ../testdata/output/FireLoc375.txt
```

A successful execution usually requires 1 minute or more, depending on the speed of your computer and the size of the input. If execution fails, you will see an error message indicating the cause of failure (e.g., a file cannot be found, or a label cannot be recognized). Correct it and run again. If the problem has some other cause, it can be identified using the log files. Log files are automatically generated within the directory used for execution. They start with `stdfile*` and `errfile*` and can be deleted after execution. Other log and intermediate files may be generated automatically within the directory used for execution. They are useful for traceability and debugging purposes. However it is strongly recommended that users clean up log files and intermediate files left behind in the run directory before initiating a fresh execution of the SPA. Intermediate files from a previous run may affect a successive run and produce ambiguous results. The 'run' can be executed from any directory the user chooses. This can be done by prefixing it with the file path for the 'run' script.

NOTES:

1. The Fire Location text file contains information about each fire pixel detected by the SPA. Each line represents one fire pixel and has the following seven columns, separated by commas:
 - Column 1: Fire Pixel Latitude
 - Column 2: Fire Pixel Longitude
 - Column 3: I04 Brightness Temperature
 - Column 4: Along scan pixel dimension (km)
 - Column 5: Along track pixel dimension (km)
 - Column 6: Fire Detection Confidence
 - Column 7: Fire Radiative Power *

* as of this release, the values in the Fire Radiative Power column are now always zero.

Please note that the Fire Location text file is not generated if no fire pixels are detected for the datasets processed. When running in standalone mode, the `VFIRE375_SPA` will terminate with a message similar to the following when no Fire Location text file is generated:

```
Output viirs.activefires375 is /home/ipopp/drl/SPA/VFIRE375/testdata/output/VF375.hdf
```

```
Output viirs.fireloc375 is null
```

2. The possible values for Column 6: Fire Detection Confidence in the Fire Location text file are as follows:
 - 7 = Low confidence fire pixel

- 8 = Nominal confidence fire pixel
 - 9 = High confidence fire pixel
3. The VIIRS M13 band SDR and VIIRS IVCDB HDF files may be optionally provided as additional inputs to enable nighttime processing for data located over the South Atlantic Anomaly; these additional inputs are not necessary for nighttime data located anywhere else. If these optional inputs are not provided for nighttime data over the South Atlantic Anomaly, the VFIRE375_SPA will terminate with a message similar to the following:

VFIRE375 outputs not generated: For nighttime passes over the South Atlantic Anomaly, viirs.svm13/viirs.ivcdb inputs are required.

Output viirs.activefires375 is null

Output viirs.fireloc375 is null

4. The data products generated by this SPA may be visualized with the DRL's H2G_SPA (Hierarchical Data Format [HDF] to Georeferenced Tagged Image File Format [GeoTIFF] Converter Science Processing Algorithm). H2G is designed specifically for Direct Readout applications to create geolocated GeoTIFF images, jpeg browse images, and png browse images for parameter datasets in SNPP products and EOS products. H2G_SPA and its User Guide are available for download from the DRL Web Portal. Please refer to Appendix A for information on enabling image production for this SPA in IPOPP.

To Use the Scripts in the testscripts Directory

One simple way to run the algorithms from the directory of your choice using your own data is to copy the run_VFIRE375.sh script from the testscripts directory to the selected directory. Change the values of the variables like WRAPPERHOME, INPUTHOME and OUTPUTHOME to reflect the file paths of the wrapper directories and the input/output file paths. Then modify the input/output file name variables. Run the script to process your data.

Appendix A SPA Services

Installation of this SPA in IPOPP mode will make the SPA services listed in Table A-1 available to IPOPP. These SPA services along with any other prerequisite SPA services (listed in Table A-2) will need to be enabled to allow IPOPP to automate production of the VFIRE375_SPA data products. The SPAs containing the prerequisite SPA services listed in Tables A-2 can be downloaded from the DRL Web Portal, in case they are not already available in your IPOPP installation. Details about these other SPAs are available in the respective SPA User's Guides. Please refer to the IPOPP User's Guide for instructions on how to install an SPA in IPOPP and enable the corresponding SPA services.

Table A-1. SPA Services

SPA services for this SPA	Data Products produced	
VFIRE375	Product Name	Destination (when installed in IPOPP)
	VIIRS 375m Active Fires	/raid/pub/gsfcddata/npp/viirs/level2/VF375_npp_dyymmdd_thhmmssS_ehhmmssS*.hdf ¹
	VIIRS 375m Fire Location Text File	/raid/pub/gsfcddata/npp/viirs/level2/FireLoc375_npp_dyymmdd_thhmmssS_ehhmmssS*.txt ¹

¹ Where *yyyy*, *mm*, *dd*, *hh* represents the year, month and day of month for the start of the swath; the first *hh*, *mm*, *ss*, *S* represents the hour, minutes, seconds and 10th of a second for the start of the swath and the second *hh*, *mm*, *ss*, *S* represents the end time of the swath.

Table A-2. Prerequisite SPA services

Prerequisite SPA services	SPA in which they are available
VIIRS_C-SDR or VIIRS-SDR	C-SDR_SPA VIIRS-SDR_SPA

NOTE: The SPA services VIIRS-SDR and VIIRS_C-SDR must never be run simultaneously.

Table A-3. Image-generating SPA services

Image-generating SPA services	SPA in which they are available
vfire375-geotiff	H2G_SPA

NOTE: Please refer to the H2G_SPA User's Guide for more details about the image products, including their locations and filename patterns when they are generated in IPOPP.